



Nederlands Meetinstituut

# Draft EC-type examination certificate

Number **T10xxx** revision 0  
Project number 607282  
Page 1 of 1

Issued by NMI Certin B.V.  
Hugo de Grootplein 1  
3314 EG Dordrecht  
The Netherlands

Notified Body number 0122

In accordance with The Metrologiewet (Stb. 2006, 137) as Dutch implementation of Directive 2004/22/EC on measuring instruments (MID).

Manufacturer Italtax s.r.l.  
Zona Industriale S. Maria in Potenza  
62017 Portorecanati (MC)  
Italy

In respect of A model of an **electronic taximeter**.  
Manufacturers name or mark: Italtax or Digitax  
Type : M1

Characteristics Mechanical environment class M3  
Electromagnetic environment class E3  
Temperature range -25 °C / +55 °C

In the description number T10xxx revision 0 further characteristics are described.

Valid until 30 October 2016

Description and documentation The taximeter is described in the description number T10xxx revision 0 and documented in the documentation folder number T10xxx-1, appertaining to this EC type-examination certificate.

Dordrecht, 30 October 2006  
NMI Certin B.V.

Ing. C. Oosterman  
Manager Product Certification


**NMI Certin BV**  
Hugo de Grootplein 1  
3314 EG Dordrecht  
PO Box 394  
3300 AJ Dordrecht, NL  
T +31 78 6332332  
F +31 78 6332309  
certin@nmi.nl  
www.nmi.nl

Parties concerned can lodge objection against this decision, within six weeks after the date of submission, to the general manager of NMI (see "Regulation objection and appeal against decisions of NMI")

This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability.

Reproduction of the complete document is permitted.





## 1 General information about the taximeter

All properties of the automatic catchweighing instrument, whether mentioned or not, may not be in conflict with the legislation.

### 1.1 Essential parts

Description	Drawing number	Rev.	Remarks
Block diagram	M1 Block diagram	--	
Exploded view	M1 Exploded View	--	
Component layout Parts list	M1 Component layout Component List	-- --	3 pages

### 1.2 Essential characteristics

Power supply	:	12 V DC.
Range of device constant	:	$k = 500 \text{ km}^{-1}$ to $65535 \text{ km}^{-1}$ ;
Resolution of device constant	:	$1 \text{ km}^{-1}$ ;
Range of time tariff	:	$0.10 \text{ }^1\text{CU/h}$ to $6553.50 \text{ CU/h}$ ;
Resolution of time tariff	:	$0.10 \text{ CU/h}$ ;
Range of distance tariff	:	$0.10 \text{ CU/km}$ to $6553.50 \text{ CU/km}$ ;
Resolution of distance tariff	:	$0.10 \text{ CU/km}$ ;
Time measuring signal frequency	:	1 Hz

#### Recalling device constant:

From "For hire": press K2 and K3 simultaneously.

#### Recalling the non-resettable counter over the device constant:

From "For hire" with button K2 (hold for 2 s) to "E-SEAL" with the K2 button. Then with K4 button to select the "E-SEAL" menu. Scroll through the menu with K4 and K3 buttons. At "Adj" (comes automatically after "-End-") the non-resettable counter over the device constant is displayed. This menu can be left by pressing the "OP" key.

---

<sup>1</sup> CU = Currency Units



Recalling applied tariffs:

From "For hire" with button K2 (hold for 2 s) to "tAr SH" with the K2 button. Then with K4 button to "Tariff Show" menu. Scroll through the menu with K4 and K3 buttons. At "d1 t1" the time tariff is displayed, at "e1 t1" the distance tariff is displayed.

Recalling the non-resettable counter over the tariffs:

From "For hire" with button K2 (hold for 2 s) to "E-SEAL" with the K2 button. Then with K4 button to select the "E-SEAL" menu. Scroll through the menu with K4 and K3 buttons. At "tAr" the non-resettable counter over the tariffs is displayed. This menu can be left by pressing the "OP" key.

The following devices can be present:

- Display check;
- Calculation mode S (single application of tariff);
- Calculation mode D (double application of tariff);
- Operating position "Measure";
- Totaliser data;
- Long term data storage.

Software specification:

Software version	Identification number (checksum)	Remarks

The software version and identification number will be displayed at start-up / after pressing the key sequence: [???

### 1.3 Essential shapes

Description	Drawing number	Rev.	Remarks
Front view	M1 inscriptions	--	
Sealing	Mechanical Sealing	--	

Markings:

- The markings have to fulfill the requirements stated in the legislation.
- The data plate is fixed to the taximeter and secured against removal by sealing or will be destroyed when removed.

To secure components that may not be dismantled or adjusted by the user, the automatic catchweighing instrument has to be secured in a suitable manner on the locations:

- First stage verification, sealing sticker over screw on backside;
- Second stage verification, see drawing Mechanical sealing, with lead or sticker seal;
- Reverification, see sealing for first and second stage verification.



The securing component has to bear either:

- A mark of the manufacturer laid down in an approved quality system by a Notified Body, or;
- A mark of a Notified Body.

#### **1.4 Conditional parts**

The taximeter may be fitted with the following peripheral devices:

- Printer, manufacture Epson, type M150 II.

The taximeter may be fitted with the following interfaces:

- Distance sensor input:
  - Low voltage: 0 – 0.3 V
  - High voltage: 5 – 12 V
  - Trigger: high-low transition

#### **1.5 Conditional characteristics**

Cut-off power supply voltage: 8.5 V DC..

#### **1.6 Non-essential parts**

The taximeter may be connected to non-essential devices, for example but not limited to card readers, seat sensors and roof lights, provided that:

- They do not present primary data;
- They do not lead to an instrument having other essential characteristics than those fixed by this type-examination document.

## **2 Approval conditions**

See chapter 1.3, essential shapes.

## **3 Seals and verification marks**

See chapter 1.2, essential characteristics and 1.3, essential shapes.